

WATERLESS VAPOR-PHASE SYSTEM FOR ODOR CONTROL



KEY FEATURES

- Patented Uniform Vapor-Distribution
- Technology ensures a consistent and controllable level of product is dispersed via pipe distribution system
- All Byers Scientific Vapor units come equipped with our integrated Cloud-based Equipment-control Platform enabling customers to remotely operate and collect real-time data from their systems from any cellphone, tablet or computer.
- All customers are granted password-protected access to their system's dedicated website via the Client Portal on the Byers Scientific web page
- UL Listed control panel is designed for site-specific electrical requirements (240 or 480 VAC, 3 Phase)
- Operational data are logged to provide evidence of compliance to local/state/ federal agencies
- Optional weather station fully integrated with Cloud-based equipment control platform
- Utilizes Ecosorb® 607 a proprietary neutralizer from OMI Industries that is formulated specifically for odors associated with the solid waste and industrial-scale composting industries
- Each system is custom designed and engineered for a client's site-specific characteristics
- Rugged weather resistant enclosure capable of withstanding prolonged exposure to wind, rain and other elements
- Service and maintenance easily accomplished with over-sized access door, removeable tank lids and exterior accessed air filter housings

WATERLESS VAPOR-PHASE SYSTEM FOR ODOR CONTROL

SPECIFICATIONS

SYSTEM OVERVIEW

Footprint 74.5" L x 59.0" D x 63" H

Decibels at 30 feet: Approx. 65 dB

Access Door with Intake Filter

- Filter Size: 18" x 18" x 1" Nominal
- (Actual: 17.75" x 17.75" x 0.75")

63 Gallon Storage Tank

- Internal circulation via eductors Level Sensor
- Temperature Sensor
- In-Tank Heater for Cold Climates Tank can be filled by toggle switch operated pump affixed to tote/drum

Evaporation Tank

- Patented Uniform Vapor Production Level Sensor
- Temperature Sensor In-Tank Heater
- Tank fills automatically via PLC

ELECTRIC

UL-LISTED PANEL

40 / 50 Amp Service Disconnect Switch
Touch Screen Panel Display

- Indicator Lights
- Programmable Logic Controller (PLC) for Critical System Operations
- Industrial Remote Access Router with External Antenna
- High Limit Heat Safety Controllers

3-PHASE COMPONENTS (208- 240 / 480VAC)

Main Blower

- 7.5 HP Motor
- 19.4 - 17.6 / 8.8 Full Load Amps
- 3530 RPM

Secondary Blower

- 0.5 HP Motor
- 3450 RPM

In-Tank Heater(s)

- 2000 - 2660 / 3500 Watts
- 5.6 - 6.4 / 4.3 Amps

115VAC COMPONENTS

- 1/10 HP Intermittent Pump Tote Transfer Pump
- 1/25 HP Pump Circulation Pump 1/30 HP Pump Transfer Pump

24VDC COMPONENTS

- Flow Meter with Totalizer
- Differential Pressure Sensor Range: 0 - 2 inH₂O
- Differential Pressure Sensor Range: 0 - 40 in H₂O
- Two (2) Liquid Level Sensors
- Two (2) Liquid Temperature Sensors



**Monitor your system
anytime, from anywhere.**

Every Byers system comes fully equipped with a dedicated Cloud-based website, putting control in your hands.